

[[“System for driving columns of a liquid crystal display.”]]

ABSTRACT

[[* * * * *]]

5 A [[The present invention refers to a]] system for driving columns of a liquid
crystal display includes [[comprising a]] logic circuitry [[(10)]] operating in a supply
path between a first [[(VDD)]] and a second [[(VSS)]] supply voltage in which the
first supply voltage is [[(VDD)]] higher than the second supply voltage [[(VSS)]].
The logic circuitry [[(10)]] is capable of generating [[starting from the]] first logic
signals [[(LOW_FRAME, WHITE_PIX) in input]] and second logic signals [[(CP,
10 CN, CP_N, CN_N) in output]] whose value is equal to the first [[(VDD)]] or second
[[(VSS)]]
supply voltage. The system includes [[device comprises]] two level shifters
[[elevator devices (11, 12)]] coupled to the logic circuitry [[(10)]] and operating in a
supply path between a third supply voltage [[(VLCD)]] greater than the first supply
voltage [[(VDD)]] and the second supply voltage [[(VSS)]]; the level shifters
15 [[elevator devices (11, 12)]] are capable of raising the value of the second logic
signals [[(CP, CN, CP_N, CN_N)]]]. The system [[device]] also includes
[[comprises]] a first [[(T11-T12)]] and a second [[(T13-T14)]] pair of transistors
having [[shaving]] different supply paths [[(VLCD-VA, VB-VSS)]] and having an
output terminal [[(OUT)]] in common; the first [[(T11-T12)]] and the second [[(T13-
20 T14)]] pair of transistors are coupled [[connected]] to the level shifters [[elevator
devices (11, 12) so as]] to determine the drive signal of a column. The system
[[device comprises]] includes turnoff circuitry [[(15)]] operating in a supply path
between the third [[(VLCD)]] and the second supply voltage [[(VSS)]] and coupled to
the two level shifters [[elevator devices (11, 12)]]]. The turnoff circuitry [[(15)]] is
25 capable of keeping one of the two pairs of transistors [[(T11-T12, T13-T14)]] in a
turnoff state in the period of time of a frame when the other of the two pairs of
transistors [[(T11-T12, T13-T14)]] is [[in]] operative [[conditions. (Fig. 5)]]].

CORRECTED VERSION

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
8 January 2004 (08.01.2004)

PCT

(10) International Publication Number
WO 2004/003882 A1

(51) International Patent Classification⁷: **G09G 3/36**

Leonardo [IT/IT]; Via Circonvallazione 9, I-11026 Pont
Saint Martin (AO) (IT).

(21) International Application Number:
PCT/EP2003/006638

(74) Agent: **MITTLER, Enrico**; Mittler & C. S.R.L., Viale
Lombardia, 20, I-20131 Milano (IT).

(22) International Filing Date: 23 June 2003 (23.06.2003)

(81) Designated States (*national*): CN, IN, JP, US.

(25) Filing Language: English

(84) Designated States (*regional*): European patent (AT, BE,
BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU,
IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

(26) Publication Language: English

(30) Priority Data:
MI2002A001424 27 June 2002 (27.06.2002) IT

Declarations under Rule 4.17:

- *as to the applicant's entitlement to claim the priority of the
earlier application (Rule 4.17(iii)) for the following desig-
nation US*
- *of inventorship (Rule 4.17(iv)) for US only*

(71) Applicants (*for all designated States except US*): **STMI-
CROELECTRONICS S.R.L.** [IT/IT]; Via C. Olivetti, 2,
I-20041 Agrate Brianza (IT). **DORA S.P.A.** [IT/IT]; Rue
de la Gare, 39, I-11024 Chatillon (IT).

Published:

- *with international search report*

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **PAPPALARDO,**
Salvatore [IT/IT]; Via Calatabiano, 38, I-95125 Catania
(IT). **PULVIRENTI, Francesco** [IT/IT]; Via Pacinotti,
15, I-95024 Acireale (IT). **PRIVITERA, Salvatore**
[IT/IT]; Via Galermo, 110, I-95123 Catania (IT). **SALA,**

(48) Date of publication of this corrected version:


3 June 2004

(15) Information about Correction:

see PCT Gazette No. 23/2004 of 3 June 2004, Section II

[Continued on next page]

(54) Title: SYSTEM FOR DRIVING COLUMNS OF A LIQUID CRYSTAL DISPLAY



(57) Abstract: The present invention refers to a system for driving columns of a liquid crystal display comprising a logic circuitry (10) operating in a supply path between a first (VDD) and a second (VSS) supply voltage in which the first supply voltage is (VDD) higher than the second supply voltage (VSS). The logic circuitry (10) is capable of generating starting from the first logic signals (LOW_FRAME, WHITE_PIX) in input second logic signals (CP, CN, CP_N, CN_N) in output whose value is equal to the first (VDD) or second (VSS) supply voltage. The device comprises two elevator devices (11, 12) coupled to the logic circuitry (10) and operating in a supply path between a third supply voltage (VLCD) greater than the first supply voltage (VDD) and the second supply voltage (VSS); the elevator devices (11, 12) are capable of raising the value of the second logic signals (CP, CN, CP_N, CN_N). The device also comprises a first (T11-T12) and a second (T13-T14) pair of transistors shaving different supply paths (VLCD-VA, VB-VSS) and having an output terminal (OUT) in common; the first (T11-T12) and the second (T13-T14) pair of transistors are connected to the elevator devices (11, 12) so as to determine the drive signal of a column. The device comprises turnoff circuitry (15) operating in a supply path between the third (VLCD) and the second supply voltage (VSS) and coupled to the two elevator devices (11, 12). The circuitry (15) is capable of keeping one of the two pairs of transistors (T11-T12, T13-T14) in a turnoff state in the period of time of a frame when the other of the two pairs of transistors (T11-T12, T13-T14) is in operative conditions.

WO 2004/003882 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.